



## LVT RESTORATIVE COATING



LVT flooring requires specialty maintenance. Rethink standard floor maintenance with **Aspida™**.

**Aspida** is a strip-free floor coating formulated to extend the life of LVT and other specialty flooring. It protects the floor, creating a soft, more natural look. **Aspida** also utilizes Microban® antimicrobial technology to inhibit the growth of product damaging microbes on the floor coating.\* Through careful manipulation of particle size and distribution, Buckeye has designed polymers and a resin system that eliminates floor stripping, prevents heavy build up, and makes floors easier to clean.



**Aspida** is formulated with Polymatrix Technology, a proprietary polymer blend that allows the coating to protect floors while eliminating the need for stripping.



Microban antimicrobial technology is built into **Aspida** to provide an added level of proactive product protection against product damaging microbes\* - keeping the floor coating cleaner, longer.

*All Microban antimicrobial technologies are approved by the US EPA for their specific use in the product in which they are used.*

### FEATURES

- Formulated with Polymatrix Technology
- Formulated with Microban® Technology
- No floor stripper required
- Protects and restores

### Available Packaging



*\*Microban technology does not protect users against disease-causing microorganisms. Microban Products Company makes neither direct nor implied public health claims. Normal cleaning practices should be maintained.*



## LVT RESTORATIVE COATING

### Directions for use

#### Preparation

##### Automatic scrubber

1. Dust mop or use a tack cloth to remove heavy dirt or soils.
2. Scrub floor using a blue pad and **Buckeye Eco® Heavy Duty Cleaner (E61)** or **XL 100™** (3 oz./gal). Pick up solution.

##### Mop and bucket or microfiber pad

1. Dust mop or use a tack cloth to remove heavy dirt or soils.
2. Mop the floor with **E61** or **XL-100**. Change microfiber pad as needed for heavily soiled surfaces.  
No rinse required.

#### Application

##### New application

1. Follow preparation steps above.
2. Apply 3 coats of undiluted product with a microfiber flat mop system and a microfiber finish mop.
3. Allow 15 minutes for drying and then repeat application. Do not rinse.

##### Routine Maintenance

1. Sweep large debris with a dust mop or tack cloth.
2. Damp mop daily with **Buckeye Eco pH Neutral Cleaner (E31)** or **Straight-Up®** to maintain a uniform look. You may also use an automatic scrubber with a white or red pad and **Buckeye Eco Floor Cleaner (E33)** or **Straight-Up** to maintain a uniform look.
3. Recoat with Aspida based on traffic recommendations below:  
*Light Traffic – Recoat as needed, one coat*  
*Moderate Traffic – Recoat every 6 months, one coat*  
*Heavy Traffic – Recoat every 3 months/quarter, one coat*

##### Restorative Maintenance

1. Follow new application steps above.
2. Recoat recommendations based on traffic recommendations below:  
*Light and Moderate Traffic – Every 12 months or as needed*  
*Heavy Traffic – Every 12 months or sooner if needed*

TECHNICAL SPECIFICATIONS	
pH	8.4 ± 0.4
Leveling	Excellent
Freeze/Thaw Stability	Passes 3 cycles
Removability	Excellent
Drying Time	10–15 minutes
Dirt Resistance	Excellent
Film Color	Water-Clear
Weight/Gallon	8.41 lbs
Slip Resistance	U.L. Classified



Microban® is a registered trademark of Microban Products Company.

BUCKEYE INTERNATIONAL, INC.

2700 WAGNER PLACE • MARYLAND HEIGHTS • MO 63043 • USA • 800.321.2583

www.buckeyeinternational.com